## **VALONA MQL 3046**





Chlorine-free neat cutting oil for microlubrication.

## **APPLICATIONS**

- VALONA MQL 3046 is a neat chlorine-free cutting oil applied by micro-spraying and intended for machining ferrous and non-ferrous metals and aluminium alloys.
- VALONA MQL 3046 is particularly suitable for processes involving milling, tapping, drilling, reaming and sawing.
- VALONA MQL 3046 is also well suited to forming operations:
  - bending and expanding of copper or aluminium alloy pipes for radiators and heat exchangers in automotive vehicles.
  - blanking operations (by spraying).

## **ADVANTAGES**

- VALONA MQL 3046 possesses enhanced lubricating properties so as to be effective in small quantities.
- VALONA MQL 3046 is a product based on plant sources selected for:
  - best possible performance,
  - excellent mist control,
  - low odour.
- Ensures cleanliness of machines and their environment.
- VALONA MQL 3046 means:
  - less lubricants used,
  - elimination of waste costs,
  - improved chip management.

TYPICAL CHARACTERISTICS	METHODS	UNITS	VALONA MQL 3046
Appearance	-	-	Clear
Colour	-	-	Light yellow
Odour	-		none
Density at 15°C	ISO 3675	kg/m³	915
Kinematic viscosity at 40°C	ISO 3104	mm²/s	46
Flash point (open vessel)	ISO 2592	°C	330
Biodegradability	CFC L-33-A-93	%	> 95

The characteristics shown in this table are typical values given for illustrative purposes.

